

DOUBLE-AXLE TRAILERS

rocking beam with cantilever leaf-springs tipper opening on three sides



STANDARD EQUIPMENT

- Smooth sheet steel floor
- Mechanical drawbar jack
- Hydraulic drawbar jack (FBN14T and FBN16T)
- Hydraulic tipping and quick coupling with limit stop valve
- Top-hinged tailboard
- Front winches
- Light system and documents for on-road registration

OPTIONAL EXTRAS

- Tipper geared pump, lt. 60 power shaft
- Tipper geared pump, lt. 100 power shaft with container lowered from driver's seat
- Tipper pump operation with hydraulic motor
- Hydraulic drawbar jack with locking valve (*FBN11)
- Embossed sheet steel floor
- Front and rear imperials
- Cereal hatch
- Top-hinged sides
- Side winches
- Tube for sheet
- Spare wheel bay
- Toolbox
- Braking corrector
- Steerable rear axle (*FBN11)

RUOTA SINGOLA

TIPO	DIMENSIONE mt PIANALE E SPONDE	PORTATA OMOL. COMPL. KG	TARA KG	RUOTE	FRENI
FBN 10T (tandem) ass. post. fisso	4,50x2,20x0,50 4,50x2,40x0,50	11800	2300	385/55R19.5 us. 13.0/55-16 PRI18	PNEUM. IDRAUL.
FBN 11/60T ass. post. fisso	4,80x2,40x0,50	6000	2800	285/55R19.5 us. 305/70R19.5 us. 385/55R19.5 us. 385/55R19.5 nv.	IDRAUL.
FBN 11T ass. post. fisso	4,80x2,40x0,50	11000	2800	285/55R19.5 us. 305/70R19.5 us. 385/55R19.5 us. 385/55R19.5 nv.	PNEUM. IDRAUL.
FBN 14T ass. post. fisso	5,50x2,40x0,60	14000	3500	435/55R19.5 us. 425/65R22.5 us.	PNEUM. IDRAUL.
FBN 16T ass. post. fisso	6,20x2,40x0,60	14000	4260	425/65R22.5 ric. 500/60R22.5 us.	PNEUM. IDRAUL.

RUOTA GEMELLA

TIPO	DIMENSIONE mt PIANALE E SPONDE	PORTATA OMOL. COMPL. KG	TARA KG	RUOTE	FRENI
FBN 11/60T ass. post. fisso	4,80x2,40x0,50	6000	2800	235/75R17.5 us. 245/70R19.5 us. 235/75R17.5 nv.	IDRAUL.
FBN 11T ass. post. fisso	4,80x2,40x0,50	11000	2800	235/75R17.5 us. 245/70R19.5 us. 235/75R17.5 nv.	PNEUM. IDRAUL.