

SINGLE-AXLE TRAILER rear tipper homologated for transporting tracked vehicles and bales type "E"

STANDARD EQUIPMENT

- UNP steel profile chassis on rigid axle
- Embossed sheet steel floor
- Hydraulic tipping with quick-coupling double-effect piston
- Mechanical drawbar jack
- Front winches
- Connectors for front and rear imperial
- Light system and documents for on-road registration

OPTIONAL EXTRAS

- Hydraulic brake
- Braking regulation valve
- Side winches
- Hydraulic drawbar jack with locking valve
- Toolbox
- Tailboard
- Openable headboard cm. 30
- Leaf-spring suspension
- Front and rear imperial for bales
- Sides on all models

TYPE	FLOOR DIMENSIONS	TOTAL HOMOLOGATED CAPACITY KG	UNLADEN WEIGHT kg.	WHEELS	BRAKES
*RC 50 single wheel	3,60x1,88 mis. est. 2,45	5000	1000	235/75R17.5 us. 10.0/75-15.3 nv.	MECC.
RP 50 twinned wheels	4,20x2,00 4,20x2,20	5000	1160	225/70R15 us. 205/65R17.5 us. 225/70R15 nv.	MECC.
RP 60 twinned wheels	4,50x2,20	6000	1130	205/65R17.5 us. 205/65R17.5 nv. 215/75R17.5 us.	IDRAUL.
FBRI TC 50 twinned wheels	4,80x2,20 4,80x2,45	5000	1400	205/75R17.5 us. 215/75R17.5 us. 215/75R17.5 nv.	MECC.
**FB 60 twinned wheels	5,00x2,20 5,00x2,45	6000	1590	205/75R17.5 us. 215/75R17.5 us. 215/75R17.5 nv.	IDRAUL.
TCS 55 twinned wheels	5,50x2,20 5,50x2,45	6000	1700	205/75R17.5 us. 235/75R17.5 us. 215/75R17.5 nv.	IDRAUL.
TCS 50 twinned wheels	6,20x2,45	5000	1800	205/75R17.5 us. 235/75R17.5 us. 215/75R17.5 nv.	MECC.
**TCS 60 twinned wheels	6,20x2,45	6000	1800	205/75R17.5 us. 235/75R17.5 us. 215/75R17.5 nv.	IDRAUL. PNEUM.
**TCS 66 twinned wheels	6,60x2,45	6000	1840	205/75R17.5 us. 235/75R17.5 us. 215/75R17.5 nv.	IDRAUL.

**Homologate even with single wheel

